



LUBRICANTS

POWER TO PERFORM

DISOLA M 3015 & DISOLA M 4015

DESCRIPTION

DISOLA M 3015 & 4015 are monograde engine oils for High and Medium speed diesel engines.

APPLICATIONS

- Oil specially devised for lubricating high and medium speed diesel engines at sea and for fishing and river transport applications
- Main and auxiliary naturally-aspirated or supercharged engines of all types and ratings
- Journals, stern tubes and reduction drives / reversing gear
- Recommended for engines running on Gas oil and Marine Diesel oil

SPECIAL FEATURES

- Meets API CF
- High detergent, dispersant and anti-wear capabilities, ensuring cleanliness and long life for engine and transmission systems
- Oil film has good mechanical and thermal strength
- High alkalinity reserve which neutralizes acid combustion products
- Excellent resistance to the action of water

PHYSICO-CHEMICAL PROPERTIES

| CHARACTERISTICS METHODS | UNITS | DISOLA | |
|------------------------------|---------------------|--------|--------|
| | | M 3015 | M 4015 |
| S.A.E GRADE | | 30 | 40 |
| Density at 15°C | Kg / m ³ | 900 | 904 |
| Kinematic viscosity at 40°C | mm ² / s | 110 | 145 |
| Kinematic viscosity at 100°C | mm ² / s | 12 | 14.2 |
| BN (ex-TBN) | mgKOH / g | 14 | 14 |

Characteristics of this chart are indicative typical values

APPROVALS

Approved by ABC, Deutz, Mireless Blackstone, HiMSEN, Mitsubishi, Niigata, Stork, Wartsila and other major engine builders.