



LUBRICANTS

POWER TO PERFORM

HP HYLUBE X-3 10W KB, 30 KB

DESCRIPTION

HP HYLUBE X-3 10W KB, 30 KB are premium quality lubricating oils formulated especially for BEML- KOMATSU. HYLUBE X-3- 10 W KB can be used as a hydraulic fluid as well.

The oils offer Excellent thermal and oxidation stability excellent performance under severe conditions

MEETS SPECIFICATIONS

API CD/CF, E-DL-2 OF BIS IS: 13656:2014 (Re-affirmed 2013) AND MIL-L-45199B and BEML-KOMATSU

PHYSICO-CHEMICAL PROPERTIES

HP HYLUBE X-3	10W(KB)	30(KB)
Kinematic Viscosity, cSt, @ 100°C	5.6	9-13
Kinematic Viscosity, cSt, @ 40°C	32-39	80-120
Viscosity Index, Min	95	90
Pour Point °C, Max	-27	-12
Sulphated Ash, % Wt, Max	1.85	1.85
TBN, mg Koh /gm, Min	10.5	10.5
Foaming Tendency/Stability ml	10	10
SEQ 1	50/10	50/10
SEQ 2	50/10	50/10
SEQ 3	50/10	50/10

Approved by Beml For Beml- Komatsu Equipment