



# LUBRICANTS

**POWER TO PERFORM**

## HP GEAR DRIVE XP 85W 140

High Quality Automotive Gear Oil for Hypoid Differentials, Rear Axles and Final Drives

### DESCRIPTION

HP GEAR DRIVE XP 85W 140 grade is a high quality extreme pressure type multi-grade automotive gear oil specifically designed to address the requirements of gears, particularly hypoid gears in passenger cars, heavy commercial vehicles and other automotive equipment operated under high-speed, shock-load; high-speed, low-torque; and low-speed, high-torque conditions.

### APPLICATIONS

HP GEAR DRIVE XP 85W 140 grade is recommended for the new generation vehicles for heavy duty service in their differentials, rear axles, live front axles and final drives.

### PERFORMANCE BENEFITS

- Excellent protection to gear components against wear under heavy loads
- Permits operation across broad temperature range
- Fuel Economy
- Longer Oil and Component Life

### MEETS OR EXCEEDS REQUIREMENTS OF

- API GL-5
- MIL-L- 2105 D
- EP type GL-5 level of IS: 1118:1992 (Re-affirmed 2008) specifications

### PHYSICO-CHEMICAL PROPERTIES

Kinematic Viscosity @ 100°C, cSt	24 – 32.5
Viscosity Index, Min	95
Flash Point, COC, °C, Min	190
Foaming Tendency/Stability, Max	
Seq I	300/0
Seq II	300/0
Seq III	300/0
Phosphorus, % wt	0.026 – 0.040