



LUBRICANTS

POWER TO PERFORM

HP KLT 15W 40

Premium Quality Diesel Engine Oil for
Off-Highway Equipment

DESCRIPTION

HP KLT 15W 40 is a premium quality diesel engine oil made from the finest paraffinic base stocks and state of art additive technology, specifically designed to address the operational severity and engine durability issues in the diesel engines employed in the off-highway equipment.

HP KLT 15W 40 provides optimum protection against valve train wear, superior piston deposit control, soot handling, oxidative thickening control.

APPLICATIONS

HP KLT 15W 40 is specifically designed to cater to stringent requirements of Engines manufactured by the Japanese OEMS like KOMATSU, KOBELCO, NISSAN, MITSUBISHI, etc.

The product is also recommended for new generation diesel engines of heavy commercial, multi utility vehicles, construction equipment & DG sets etc., based on Euro III and Euro IV platforms.

FEATURES & BENEFITS

- Exceptional soot dispersancy to control oil thickening, unmatched wear control & protection to engine components against acidic corrosion
- Keeps engine clean with its improved detergency
- Low oil consumption
- Longer oil drain period

MEETS OR EXCEEDS REQUIREMENTS OF

- API CI-4
- JASO DH-1
- Volvo VDS-3
- MAN M 3275
- MTU Type 2

PHYSICO-CHEMICAL PROPERTIES

Kinematic Viscosity @ 100°C, cSt	14.0 – 16.0
Viscosity Index, Min	130
TBN, mg KOH/gm	9.0
Flash Point, COC, °C, Min	210
Pour Point, °C, Max	-21