



LUBRICANTS

POWER TO PERFORM

HP MILCY SYNTHETIC 15W 40

Premium Quality Synthetic Diesel
Engine Oil

DESCRIPTION

HP MILCY SYNTHETIC 15W 40 grade is a premium quality diesel engine oil made from the synergistic blend of Group IV synthetic base stocks, the PAOs and highly paraffinic Group II mineral base stocks along with a carefully selected high performance additive system to deliver superlative performance benefits in highly demanding modern engines powering HCVs/MUVs/LCVs etc.

HP MILCY SYNTHETIC 15W 40 provides optimum protection for control of corrosive wear tendencies, low and high temperature stability, soot handling properties, piston deposit control, valve train wear, oxidative thickening. The synthetic Group IV base stocks provide highly stable engine oil that stays in grade for a long drain interval.

APPLICATIONS

HP MILCY SYNTHETIC 15W 40 grade is recommended for new generation diesel engines of heavy commercial, multi utility vehicles, construction equipment & DG sets as well as small cars requiring high quality engine oils.

FEATURES & BENEFITS

- Protects engine from excessive wear
- Longer life for cylinder liner, piston ring, valves, cam
- Appreciably long oil life due to excellent viscosity control
- Higher levels of engine cleanliness
- Helps to reduce pollution

MEETS OR EXCEEDS REQUIREMENTS OF

- API CH – 4/CG-4
- ACEA A3/B3/E5/E3
- VOLVO VDS 2
- MB 228.3
- Cummins CES 20076

PHYSICO-CHEMICAL PROPERTIES

Kinematic Viscosity @ 100°C, cSt	14.3 – 15.3
Viscosity Index, Min	120
TBN, mg KOH/gm, Min	9.0
Flash Point, COC, °C, Min	210
Pour Point, °C, Max	-24