



LUBRICANTS

POWER TO PERFORM

HP SUPERTRAN HVI

Super-Premium quality Universal
Tractor Transmission Oil (UTTO)

DESCRIPTION

HP SUPERTRAN HVI grade is a super-premium quality Universal Tractor Transmission Oils (UTTO) formulated from high quality hydrotreated base stocks and carefully selected additives, designed to deliver the best performance in Transmission, Hydraulic, Final Drive and PTO systems of modern tractors.

APPLICATIONS

HP SUPERTRAN HVI grade is recommended for use in tractors manufactured by all major OEMs like MAHINDRA & MAHINDRA, TAFE, EICHER, SAME, SWARAJ, ESCORTS, JOHN DEERE etc.

The product can also be used in other off-road/construction equipment requiring UTTO type transmission fluid.

FEATURES & BENEFITS

- Balanced lubricity and other functional properties
- Unmatched low and high temperature properties due to its high viscosity index
- Unmatched performance in operation of wetbrake mechanisms
- Minimizes clutch-plate wear and brake chatter
- Provides excellent lubrication for gear box and transmission equipment
- Minimizes wear in high pressure hydraulic pump systems
- Superior oxidation and deposit control to render new-like performance for longer service intervals
- Superior protection against Rust and Corrosion

MEETS OR EXCEEDS REQUIREMENTS

- John Deere : JDM J20 C/D
- Massey Ferguson : CMS M 1135/ M 1141/M 1143/ M 1145
- Case New Holland: MAT 3505/ 3509/ 3525
- Ford: ESN-M2C86-B/C, ESN-M2C134-C
- Kubota: UDT Fluid
- Fendt
- Allison C-4
- Caterpillar TO-2
- AGCO Powerfluid 821X
- ZF: TE-ML 03E/05F/06K/17E/21F



LUBRICANTS

POWER TO PERFORM

HP SUPERTRAN HVI

Super-Premium quality Universal
Tractor Transmission Oil (UTTO)

PHYSICO-CHEMICAL PROPERTIES

Kinematic Viscosity @ 100°C, cSt	10.0 – 12.5
Viscosity Index, Min	150
Pour Point, °C, Min	-36
Flash point (COC), °C, Min	200
Zinc, % wt	0.134 – 0.164