



LUBRICANTS™

POWER TO PERFORM™

HP X-3 30 KLT

Premium Quality Power Train Oil for
Komatsu Equipment

DESCRIPTION

HP X-3 30 KLT grade is a premium quality Power Train Oil formulated from high quality hydro-treated base stocks and carefully selected additives, designed to meet the stringent Komatsu specifications.

HP X-3 30 KLT provides optimum protection against wear, rust & corrosion, and oxidation to swing machinery, damper case and final drive.

APPLICATIONS

HP X-3 30 KLT grade is specifically designed to cater to stringent requirements of equipment manufactured by Komatsu. The product is approved by KOMATSU for their PC71, PC130-7, PC200-6, PC300-7, PC400-7 etc.

FEATURES & BENEFITS

- Excellent Anti-wear performance for protection of final drives, gears and bearings
- Balanced friction coefficient to prevent overheating and thermal cracking of transmission clutch, brake, disks and plates
- Unmatched Anti-corrosion & ant-rust performance to ensure protection to critical components like bearings, gears and hydraulic pump components
- Good seal compatibility

MEETS REQUIREMENTS OF

- API CF
- KES 07.851
- KES 07.802

PHYSICO-CHEMICAL PROPERTIES (TYPICAL)

Kinematic Viscosity @ 100°C, cSt	9.0 – 13.0
Viscosity Index	97
TBN, mg KOH/gm	10.3
Flash Point, COC, °C	230
Pour Point, °C	-27