



LUBRICANTS

POWER TO PERFORM

HYLUBE MILCY 30, 40, 50

DESCRIPTION

HYLUBE MILCY 30,40,50 are superior quality, heavy duty diesel engine lubricating oils.

Meets API CF/SF , MIL-L-2104C,E-DL 3/SF + MACK T7 OF IS: 13656:2014 (Re-affirmed 2013) and MACK T-7 engine test requirements.

Recommended for heavy commercial vehicles, light commercial vehicles, tractors, diesel passenger cars and jeeps requiring monograde oils.

- Extended TBN reserves
- Prevents oil thickening and enhances oil life
- Control of corrosive wear
- Exceptional thermal & oxidation stability
- Prolonged engine life & enhanced drain period
- Outstanding engine cleanliness

PHYSICO-CHEMICAL PROPERTIES

HYLUBE MILCY	30	40	50
Kinematic Viscosity, @ 100°C, cSt	10.3-11.5	13.5-15.2	17.5-24
Viscosity Index, Min	95	95	95
Flash Point, (COC) °C, Min	215	215	220
Pour Point, °C, Max	-6	-6	-6
Sulphated Ash, %wt, Max	1.6	1.6	1.6
TBN, mg KOH/g, Min	9.5	9.5	9.5